

## CLAIMS

1. A drill bit comprising:

a cutting blade chip formed by a cemented carbide block body, the cutting blade chip having a plurality of cutting blades arranged in a circumferential direction of the cutting blade chip to extend radially outward, the cutting blades being each structured to have a cutting edge formed by an edge between a face and a flank of the cutting blades, the cutting edges extending radially outward such that tip ends are positioned on a tip end portion of the cutting blade chip,

wherein a groove is configured to be provided in a center portion of the cutting blade chip in contact with tip ends of the cutting edges, and the tip ends of the cutting edges have pointed portions.

2. The drill bit according to claim 1, wherein the groove is formed to cross an axis of the drill bit at a substantially right angle,

the groove is structured to have a face of a circular-arc shape as viewed from a side such that a width of the groove increases from a deepest point thereof toward the tip end of the cutting edge.

3. The drill bit according to claim 1 or 2, wherein the cutting blades are formed by three cutting blades arranged at uniform intervals in a circumferential direction thereof,

the three cutting blades are structured such that the pointed portion of the tip end of the cutting edge of one of the three cutting blades is positioned at one end portion of the groove, and the pointed

portions of the tip ends of the cutting edges of remaining cutting blades are positioned at intermediate portions of the groove, and

an opposite end portion of the groove is positioned in a concave portion formed between a face and a flank of associated cutting blades.